

EverFocus Quick Reference Guide - Analog Color Cameras

Category	Polestar II Series Wide Dynamic & True Day/Night				Polestar Series	PTZ Speed Domes		
Model No.	ED610 	 EQ610	EZ610* 	 EZ630*	EZ550 	EPTZ100 	EPTZ3100/ EPTZ3100i  	EPTZ3600 
Description	Outdoor Vandal Dome w/Wide Dynamic & True Day/Night **	Box Housing w/Wide Dynamic & True Day/Night	Outdoor Bullet Style w/Wide Dynamic & True Day/Night	IR Outdoor Bullet Style w/Wide Dynamic & True Day/Night	Outdoor Bullet Style Super Low Lux w/True Day/Night	Day/Night Indoor Mini PTZ	Outdoor/Indoor PTZ w/Wide Dynamic & True Day/Night	Outdoor PTZ w/Wide Dynamic & True Day/Night
Lens	Vari-focal f=2.8~10mm f=9~22mm	Lens Sold Separately	Motorized Vari-focal Auto Iris 2.8-10mm or 9-22mm	Motorized Vari-focal Auto Iris 2.8-10mm or 9-22mm	Motorized Lens Control Vari-focal f=6~50mm	f=3.8mm (Wide)~38mm (tele) 10x Optical/10x Digital	f=3.3mm (Wide)~99mm (tele) 30x Optical/8x Digital	f=3.4mm (Wide)~122.4mm (tele) 36x Optical/12x Digital
Image Device	1/3" Sony Super HAD CCD II	1/3" Sony Super HAD CCD II	1/3" Sony Super HAD II CCD	1/3" Sony Super HAD II CCD	1/3" Sony Super HAD CCD	1/4" Sony Super HAD CCD	1/4" Sony Interline Transfer Super HAD CCD	1/4" Sony ExView Super HAD CCD
Horizontal Resolution	560 TVL	560 TVL	560 TVL	560 TVL	560 TVL	520 TVL	520 TVL	530 TVL
Picture Format	768x494 NTSC	768x494 NTSC	768x494 NTSC	768x494 NTSC	768x494 NTSC	768x494 NTSC	768x494 NTSC	768x494 NTSC
Video Output	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, (sync. negative)	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm
Sensitivity	0.0002 Lux (SENS-UP x256) 0.05 Lux/F=1.2 (AGC On)	0.0002 Lux (SENS-UP x256) 0.05 Lux/F=1.2 (AGC On)	0.0002 Lux (SENS-UP x256) 0.05 Lux/F=1.2 (AGC On)	0.0002 Lux (SENS-UP x256) 0.05 Lux/F=1.2 (AGC On) 0 Lux (IR on)	0.002 Lux (SENS-UP x128) 0.25 Lux/F=1.2	0.005 Lux (DSS x128) 0.7 Lux/F=1.8 (50IRE-color) 0.02 Lux/F=1.8 (50IRE - b/w)	Normal: 0.4 Lux Night Mode: 0.08 Lux (ICR On)	Normal: 1.4 Lux Night: 0.01 Lux (ICR On)
S/N Ratio	Over 52dB (AGC Off)	Over 52dB (AGC Off)	Over 52dB (AGC Off)	Over 52dB (AGC Off)	Over 50dB (AGC Off)	Over 50dB	50dB	50dB
Backlight Comp.	BLC/OFF/HS BLC Selectable	BLC/OFF/HS BLC Selectable	BLC/OFF/HS BLC Selectable	BLC/OFF/HS BLC Selectable	Off/Low/Middle/High	Adjustable 3 steps/Off	Yes (Off/Low/Mid/High)	Yes (Off/On)
Auto Gain Control	Low/Middle/High Selectable	Low/Middle/High Selectable	Low/Middle/High Selectable	Low/Middle/High Selectable	Off/Low/Middle/High	Adjustable 3 steps/Off	Yes (Off/Low/Mid/High)	Yes (Auto/Manual)
OSD Menu	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Sync. Mode	Internal / Line Lock External Sync.	Internal / Line Lock External Sync.	Line Lock / Internal Sync.	Line Lock / Internal Sync.	Line Lock / Internal Sync.	Internal Sync.	Internal Sync.	Internal Sync.
Power Source	12VDC/24VAC	12VDC/24VAC	12VDC/24VAC	12VDC/24VAC	24VAC	24VAC	24VAC	24VAC
Power Consumption (max.)	24VAC: 3W 12VDC: 3W	24VAC: 3W 12VDC: 3W	24VAC: 3W/6W (w/heater) 12VDC: 2.5W/5W (w/heater)	24VAC: 3W/12W (w/heater & IR) 12VDC: 2.5W/10W (w/heater & IR)	20W (w/heater) 13W (w/out heater)	19W (w/PTZ motor) 12W (w/out PTZ motor)	21W max.	21W max.
Dimension	4.8" x 4.2" (W x H)	4.7" x 2.7" x 2.2" (L x W x H)	12.5" x 4.2" x 3.2" (L x W x H) (sunshield included)	12.5" x 4.2" x 3.2" (L x W x H) (sunshield included)	10.8" x 4.5" (L x W)	8" x 4.5" (H x D)	7.1" x 11" (EPTZ3100) 6.3" x 9.1" (EPTZ3100i)	7.1" x 11" (W x H)
Weight	1.6 lbs	0.6 lbs	2.275 lbs	2.275 lbs	4.4 lbs (no bracket) 5.5 lbs (w/bracket)	3.3 lbs	6.6 lbs	6.6 lbs
Operating Temp.	14°F ~ 122°F	32°F ~ 122°F	-40°F ~ 122°F	-40°F ~ 122°F	-40°F ~ 122°F	32°F ~ 104°F	-40°F ~ 122°F (EPTZ3100) 14°F ~ 122°F (EPTZ3100i)	-40°F ~ 122°F
Vandal Resistant	Yes	No	Yes	Yes	Yes	No	No	No
Weatherproof	IP66 Rated	No	IP66 Rated	IP66 Rated	IP66 Rated	No	IP66 Rated (EPTZ3100 only)	IP66 Rated
Heater	No	No	Yes	Yes	Yes	No	No	No
Day/Night	Yes, color in low-light or True Day/Night	Yes, color in low-light or True Day/Night	Yes, color in low-light or True Day/Night	Yes, color in low-light or True Day/Night	Yes	Yes	Yes	Yes
Wide-Dynamic	Yes	Yes	Yes	Yes	No	No	Yes	Yes
Optional Accessories	BA-EDMS Mounting L-Bracket	BA-01 or BA-03 Mounting Bracket	—	—	EIR100 IR Illuminator, EZ-CMB "J" Style Bracket	EPTZ100-WLM wall mount or EPTZ100-CPM pendent mount	EPTZWBM (wall), EPTZPLM (pole), EPTZCN (corner) or EPTZCLM (ceiling) brackets	EPTZWBM (wall), EPTZPLM (pole), EPTZCN (corner) or EPTZCLM (ceiling) brackets



* Available in stock soon

** Also available in white or black colored housings

EverFocus Quick Reference Guide - Analog Color Cameras

Category	Outdoor Vandal Domes					Bullet Style Cameras			Box Type
Model No.	EHD650 	EHD525EX 	EHD350 	EHD300 	EMD300* 	EZ350 	EZ600* 	EM-C500NHWX 	EQ350 
Description	Wide Dynamic, True Day/Night Vandal Dome	True Day/Night Vandal Dome w/ExView	Vandal Dome	Vandal Dome	Mobile/Fixed, Day/Night Mini Vandal Dome **	Bullet Style Weatherproof	Mini Bullet w/Wide Dynamic & Vari-Focal Lens **	Discreet Mini Cylinder Style	Indoor Aluminum Box Housing
Lens	Vari-focal f=2.9~10mm	f=9~22mm f=2.9~10mm	f=9~22mm f=2.9~10mm	f=9~22mm f=2.9~10mm	f=3.6mm	f=3.8~9.5mm/F=1.2 f=9~22mm/F=1.6	f=3.5~16mm	f=3.6mm	Lens Sold Separately
Image Device	1/3" Pixim Digital Pixel System	1/3" Sony ExView Super HAD CCD	1/3" Sony Interline Transfer Super HAD CCD	1/3" Sony Interline Transfer Super HAD CCD	1/3" Sony Super HAD II CCD	1/3" Sony Interline Transfer Super HAD CCD	1/3" Sony Super HAD CCD II	1/3" Sony ICX638 Super HAD CCD	1/3" Sony Interline Transfer Super HAD CCD
Horizontal Resolution	480 TVL	560 TVL	560 TVL	520 TVL	550 TVL	560 TVL	560 TVL	550 TVL	560 TVL
Picture Format	768x494 NTSC	768x494 NTSC	768x494 NTSC	768x494 NTSC	768x494 NTSC	768x494 NTSC	768 x 494 NTSC	768x494 NTSC	768x494 NTSC
Video Output	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm
Sensitivity	0.08 Lux/F=1.2 (DSS x36)	0.1 Lux/F=1.2	0.5 Lux/F=1.2	0.4 Lux/F=1.2	0.05 Lux/F=1.2 (AGC On)	0.5 Lux/F=1.2	0.0002 Lux (SENS-UP x256) 0.05 Lux/F=1.2 (AGC On)	0.2 Lux/F=2.0	0.5 Lux/F=1.2
S/N Ratio	Over 48dB	Over 50dB (AGC Off)	Over 48dB (AGC Off)	Over 48dB (AGC Off)	Over 45dB (AGC Off)	Over 48dB (AGC Off)	Over 50dB (AGC Off)	Over 45dB (AGC Off)	Over 48dB (AGC Off)
Backlight Comp.	On/Off Switch	On/Off Switch	On/Off Switch	On/Off Switch	—	On/Off Switch	Off/BLC/HSBLC	Auto	On/Off Switch
Auto Gain Control	Yes (48dB max.)	On/Off Switch	On/Off Switch	On/Off Switch	Yes	On/Off Switch	Off/Low/Middle/High	Auto	On/Off Switch
OSD Menu	Yes	No	No	No	No	No	Yes, w/built-in joystick	No	No
Sync. Mode	Line Lock / Internal Sync.	Line Lock / Internal Sync.	Line Lock / Internal Sync.	Line Lock / Internal Sync.	Internal Sync.	Line Lock / Internal Sync.	Internal Sync.	Internal Sync.	Line Lock / Internal Sync.
Power Source	24VAC	12VDC/24VAC	12VDC/24VAC	12VDC/24VAC	12VDC	12VDC/24VAC	12VDC/24VAC	12VDC	12VDC/24VAC
Power Consumption (max.)	6W 20.5W (w/heater)	24VAC: 6W/20.5W (w/heater) 12VDC: 4W/11.5W (w/heater)	24VAC: 6W/20.5W (w/heater) 12VDC: 4W/11.5W (w/heater)	24VAC: 4W 12VDC: 2W	1.2W	24VAC: 6W/12.5W (w/heater) 12VDC: 4W/7.5W (w/heater)	12VDC: 2.04W 24VAC: 1.8W	1.08W	24VAC: 7W 12VDC: 4.5W
Dimension	5.1" x 3.9" x 5.1" (W x H x D)	5.1" x 3.9" x 5.1" (W x H x D)	5.1" x 3.9" x 5.1" (W x H x D)	5.1" x 3.9" x 5.1" (W x H x D)	3.19" x 2.48" (D x H)	6.8" x 3.3" x 2.8" (L x W x H)	1.14" X 4.8" - (w/out sunshield & bracket)	2.2" x 0.75" x 0.75" (L x W x H)	5.5" x 2" x 2.3" (L x W x H)
Weight	3.7 lbs	3.7 lbs	3.7 lbs	3.7 lbs	0.55 lbs	1.1 lbs	0.55 lbs	0.2 lbs	1.1 lbs
Operating Temp.	-40°F ~ 122°F	-40°F ~ 122°F	-40°F ~ 122°F	14°F ~ 122°F	14°F ~ 122°F	-40°F ~ 122°F	14°F ~ 122°F	14°F ~ 122°F	32°F ~ 122°F
Vandal Resistant	Yes	Yes	Yes	Yes	Yes	No	No	No	No
Weatherproof	IP66 Rated	IP66 Rated	IP66 Rated	IP66 Rated	IP66 Rated	IP66 Rated	IP67 Rated	IP67 Rated	No
Heater	Yes	Yes	Yes	No	No	Yes	No	No	No
Day/Night	Yes	Yes	No	No	Switches to B/W in low light	No	Yes, color in low-light or Day/Night	No	No
Wide-Dynamic	95dB typical (120dB max.)	No	No	No	No	No	Yes	No	No
Optional Accessories	BA-EHD Mounting L-Bracket	BA-EHD Mounting L-Bracket	BA-EHD Mounting L-Bracket	BA-EHD Mounting L-Bracket	—	—	—	—	BA-01 or BA-03 Mounting Bracket

* Available in stock soon

** Also available in white or black colored housings



EverFocus Quick Reference Guide - Analog Color Cameras







Cameras	Indoor Domes			Infrared Cameras						
EQ300E/EQ200E	ED350	ED300	EMW330*	EZ430	ED335	EBD430	EHD-500IR	ECZ330/ECZ230	EZ330E/ EZ335E	ED230/ ED330
										
Indoor Aluminum Box Housing	Indoor Mini Dome	Indoor Mini Dome	IR Mobile Wedge Camera	Bullet Style IR Camera	Indoor 3-Axis IR Dome, True Day/Night w/Surface or Flush Mount **	Outdoor 3-Axis IR, w/True Day/Night & Vari-focal Lens	Outdoor Vandal, 3-Axis IR Dome	Mini IR Bullet **	Long Range IR Bullet	Indoor IR Mini Dome
Lens Sold Separately	f=3.8~9.5mm f=9~22mm	f=3.7~12mm	f=3.6mm	f=2.9~10mm f=9~22mm	f=2.8~10mm f=9~22mm	f=2.9~10mm f=9~22mm	f=2.6~11mm	f=4.3mm f=6mm f=8mm	6 or 8mm (EZ230E) 8, 16 or 25mm (EZ235E)	4.3mm
1/3" Sony Interline Transfer Super HAD CCD	1/3" Sony Interline Transfer Super HAD CCD	1/3" Sony Interline Transfer Super HAD CCD	1/3" Sony Super HAD CCD	1/3" Sony Super HAD CCD	1/3" Sony Super HAD CCD	1/3" Sony Super HAD CCD II	1/3" Sony Super HAD CCD w/HQ1 Chipset	1/3" Sony Interline Transfer Super HAD CCD	1/3" Sony Interline Transfer Super HAD CCD	1/3" Sony Interline Transfer Super HAD CCD
520 TVL (EQ300E) 380 TVL (EQ200E)	560 TVL	520 TVL	520 TVL	520 TVL	520 TVL	520 TVL	550 TVL	380 TVL (ECZ230) 520 TVL (ECZ330)	520 TVL	380 TVL (ED230) 480 TVL (ED330)
768x494 (EQ300E) 510x492 (EQ200E)	768x494 NTSC	768x494 NTSC	768x494 NTSC	768x494 NTSC	768x494 NTSC	768x494 NTSC	768x494 NTSC	510x492 (ECZ230) 768x494 (ECZ330)	768x494 NTSC	510x492 (ED230) 768x494 (ED330)
BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm
0.4 Lux/F=1.2 (EQ300E) 0.3 Lux/F=1.2 (EQ200E)	0.5 Lux/F=1.2	0.4 Lux/F=1.2	0.4 Lux (IR Off) 0 Lux (IR On)	0.4 Lux (IR Off) 0 Lux (IR On)	0.4 Lux (IR Off) 0 Lux (IR On)	0.08 Lux (IR Off) 0 Lux (IR On)	0.2 Lux/F=2.0 0 Lux (LED on)	0.3 Lux/F=1.2 (ECZ230) 0.4 Lux/F=1.2 (ECZ330) 0 Lux (LED on)	0.4 Lux/F=1.2 0 Lux (LED on)	0.3 Lux/F=1.2 (ED230) 0.4 Lux/F=1.2 (ED330) 0 Lux (LED on)
Over 48dB (AGC Off)	Over 48dB (AGC Off)	Over 48dB (AGC Off)	Over 48dB (AGC Off)	Over 48dB (AGC Off)	Over 48dB (AGC Off)	Over 48dB (AGC Off)	Over 45dB (AGC Off)	Over 48dB (AGC Off)	Over 48dB (AGC Off)	Over 48dB
On/Off Switch	On/Off Switch	On/Off Switch	Yes	On/Off Switch	Yes	Yes	On/Off Switch	On/Off Switch	On/Off Switch	On/Off Switch
On/Off Switch	On/Off Switch	On/Off Switch	Yes	On/Off Switch	On	Yes	Min./Max.	On/Off Switch	On/Off Switch	On/Off Switch
No	No	No	No	No	No	No	No	No	No	No
Internal Sync.	Internal Sync.	Internal Sync.	Internal Sync.	Internal Sync.	Internal Sync.	Internal Sync.	Internal Sync.	Internal Sync.	Internal Sync.	Internal Sync.
12VDC/24VAC	12VDC/24VAC	12VDC/24VAC	12VDC	12VDC/24VAC	12VDC/24VAC	12VDC/24VAC	12VDC/24VAC	12VDC	24VAC	12VDC
24VAC: 2.2W 12VDC: 1.6W	24VAC: 5W 12VDC: 3.5W	24VAC: 4.5W 12VDC: 2.5W	8.4W (heater & IR On)	24VAC: 12W 12VDC: 15W (heater & IR On)	24VAC: 6.5W 12VDC: 6W	24VAC: 9.5W 12VDC: 9W (Heater & IR On)	24VAC: 12W 12VDC: 8.76W	3W	16W	2.4W (IR On) 1.2W (IR Off)
4.9" x 2.3" x 2.2" (L x W x H) 0.55 lbs	4.2" x 3.1" (W x H) 0.7 lbs	4.2" x 3.1" (W x H) 0.7 lbs	4.1" x 5.5" x 2.5" (W x D x H) 1.32 lbs	9.3" x 3.5" x 6.9" (L x W x H) 2.53 lbs	Surface: 5.5" x 5.1" Ceiling: 5.5" x 2.8" 1.45 lbs	4.6" x 5.7" x 5.5" (W x H x D) 2.87 lbs	5.9" x 4.5" (W x H) 3.2 lbs	2.2" x 2.4" (W x H) 0.6 lbs (w/bracket) 0.4 lbs (w/out bracket)	10.8" x 4.5" (L x W) 4.4 lbs (w/out bracket) 5.5 lbs (w/bracket)	4.3" x 3.1" (W x H) 0.4 lbs
32°F ~ 122°F	32°F ~ 104°F	32°F ~ 104°F	-40°F ~ 140°F	-40°F ~ 122°F	32°F ~ 104°F	-40°F ~ 122°F	14°F ~ 113°F	14°F ~ 122°F	-40°F ~ 122°F	32°F ~ 122°F
No	No	No	Yes	Yes	No	Yes	Yes	No	Yes	No
No	No	No	IP67 rated	IP66 rated	No	IP66 Rated	IP66 Rated	IP66 Rated	IP66 Rated	No
No	No	No	Yes	Yes	No	Yes	No	No	Yes	No
Simple Day/Night	No	Simple Day/Night	True Day/Night with ICR	Yes	True Day/Night w/IR	True Day/Night w/IR	IR	IR	IR	IR
No	No	No	No	No	No	No	No	No	No	No
BA-01 or BA-03 Mounting Bracket	BA-ED Mounting L-Bracket	BA-ED Mounting L-Bracket	—	—	—	—	—	—	—	BA-ED L-Style Mount Bracket



* Available in stock soon

** Also available in white or black colored housings

EverFocus Quick Reference Guide - Analog Color Cameras

Category	Covert Cameras					
Model No.	EM-500NHP1	EM-500NHP3	EM-500NHP4	ESD200	EM200	EB200
						
Description	Metal Case w/Conical Pinhole	Metal Case w/Flat Pinhole	Metal Case w/Super Cone Pinhole	Fake Smoke Detector	Metal Case	Camera Module
Lens	f=3.7mm	f=3.7mm	f=4.3mm	f=4.3/F=2.0	f=3.6mm*	f=3.6mm*
Image Device	1/3" Sony ICX638 Super HAD CCD	1/3" Sony ICX638 Super HAD CCD	1/3" Sony ICX638 Super HAD CCD	1/3" Sony Interline Transfer Super HAD CCD	1/3" Sony Interline Transfer Super HAD CCD	1/3" Sony Interline Transfer Super HAD CCD
Horizontal Resolution	550 TVL	550 TVL	550 TVL	380 TVL	380 TVL	380 TVL
Picture Format	768x494 NTSC	768x494 NTSC	768x494 NTSC	510x492 NTSC	510x492 NTSC	510x492 NTSC
Video Output	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm	BNC 1.0Vp-p, 75ohm
Sensitivity	0.2 Lux/F=2.0	0.2 Lux/F=2.0	0.2 Lux/F=2.0	0.3 Lux/F=1.2	0.3 Lux/F=1.2	0.3 Lux/F=1.2
S/N Ratio	Over 45dB (AGC Off)	Over 45dB (AGC Off)	Over 45dB (AGC Off)	Over 48dB (AGC On)	Over 48dB	Over 48dB
Backlight Comp.	Auto	Auto	Auto	On/Off Switch	On/Off Switch	On/Off Switch
Auto Gain Control	Auto	Auto	Auto	On/Off Switch	On/Off Switch	On/Off Switch
OSD Menu	No	No	No	No	No	No
Sync. Mode	Internal Sync.	Internal Sync.	Internal Sync.	Internal Sync.	Internal Sync.	Internal Sync.
Power Source	12VDC	12VDC	12VDC	12VDC	12VDC	12VDC
Power Consumption (max.)	1.08W	1.08W	1.08W	1.2W	2.4W	2.4W
Dimension	1" x 1" (W x H)	1" x 1" (W x H)	1" x 1" (W x H)	5.9" x 2" (W x H)	1.7" x 2.3" (W x H)	1.3" x 1.3" (W x H)
Weight	0.07 lbs	0.07 lbs	0.07 lbs	0.7 lbs	0.3 lbs	0.1 lbs
Operating Temp.	14°F ~ 113°F	14°F ~ 113°F	14°F ~ 113°F	32°F ~ 122°F	32°F ~ 122°F	32°F ~ 122°F
Vandal Resistant	No	No	No	No	No	No
Weatherproof	No	No	No	No	No	No
Heater	No	No	No	No	No	No
Day/Night	No	No	No	No	No	No
Wide-Dynamic	No	No	No	No	No	No
Optional Accessories	—	—	—	ESB200/N-4 (additional color cameras, 4.3mm lens)	—	—

*Also available with 2.5mm, 4.3mm, 6mm, 8mm, 12mm and 16mm lens

CCTV Lenses	
Auto Iris & Vari-focal Lenses	
Model No.	Description
EFV-2812DC	Vari-focal 2.8~12mm auto iris
EFV-358	Vari-Focal 3.5~8.0mm manual iris
EFV-358DC	Vari-Focal 3.5~8.0mm auto iris
EFV-416	Vari-Focal 4~16mm manual iris
EFV-416DC	Vari-Focal 4~16mm auto iris
EFV-550	Vari-Focal 5~50mm manual iris
EFV-550DC	Vari-Focal 5~50mm auto iris
Mounting Brackets	
Dome Brackets	
Model	Description
BA-ED	Plastic "L" style mounting bracket for ED series mini domes. 146.7 x 121 x 66 mm / 5.75" x 4.75" x 2.6" (L x W x H)
BA-EHD	Aluminum "L" style mounting bracket for EHD series vandal domes. 169 x 146 x 110 mm / 6.7" x 5.7" x 4.3" (L x W x H)
BA-EDMS	Aluminum "L" style mounting bracket for ED550, ED560, EDN800. 169 x 146 x 110 mm / 6.7" x 5.7" x 4.3" (L x W x H)
BA10	Ceiling mount bracket for EPD200 (624 mm / 24.6" long)
BA11	Ceiling mount bracket for EPD200 (300 mm / 12" long)
Box Camera Brackets	
Model No.	Description
BA-01	Mounting bracket. Aluminum. Max. load: 3 kg / 6.6 lbs 57 x 165 mm / 2.2" x 6.5" (W x H)
BA-03	Mounting bracket. Plastic. Max. load: 3.5 kg / 7.7 lbs 80 x 160 mm / 3.1" x 6.3" (W x H)
BA-05	Mounting bracket. Aluminum. Max. load: 10 kg / 22 lbs 84 x 294 mm / 3.3" x 11.6" (W x H)
IR Bullet Camera Brackets	
Model	Description
EZ-CMB	"J" style ceiling mount bracket for EZ Series (EZ230E, EZ235E, EZ330E, EZ335E, EZ550). Aluminum, stainless steel 200 x 278.5 mm / 7.8" x 10.9" (W x H)
PTZ Accessories	
Model	Description
EKB500	Multi-Function Keyboard Controller
EKB200	USB Keyboard Controller, 3-Axis
EPTZ-PBOX	External Power Connection Box for PTZ Cameras
EPTZ-WMB	Wall Mount Bracket for EPTZ3600/3100/3100i
EPTZ-CMB	Concrete Ceiling Mount Adaptor (included w/EPTZ3100i only)
EPTZ-BKA	Wall/Pendent Mount Adaptor (included w/EPTZ3600/3100 only)
EPTZ-SSM	Outdoor Sunshield
EPTZ-ICM	Flush In-Ceiling Mount
EPTZ-CNM	Corner Mount Adaptor with Cable Outlet
EPTZ-CLM	Indoor Pendent Mount Bracket
EPTZ-PLM	Pole Mount Adaptor with Cable Outlet
EPTZ-PBM	Adaptor for EPTZ-PBOX
ESDA-1000	Step Down Adaptor
EPTZ100-WLM	Indoor Wall Mount (for EPTZ100 only)
EPTZ100-CPM	Indoor Pendent Mount (for EPTZ100 only)
EPTZ100-PS	Power Supply (for EPTZ100 only)

